

Technical Drawing Unit: mm



Description:

Rated voltage up to 660V (50/60Hz)
Rated current: Series is rated up to 95A
Comply with IEC60947-4-1/ CE

Application: Suitable for making, breaking and frequently starting AC motors. Combined with the auxiliary contact block, time delay & machine-interlocking device, it becomes the delay contactor, mechanical interlocking contactor and star-delta starter. With a thermal relay, it combines into the electromagnetic starter.

Code \ Specs	A	B	C	D	E	a	b	Φ
CONT/D4011-5011	77	129	116	145	165	40	100/110	6.5
CONT/D6511	77	129	116	145	165	40	100/110	6.5
CONT/D8011-9511	87	129	127	175	195	40	100/110	6.5

Code: CONT/D4011, CONT/D5011, CONT/D6511, CONT/D8011, CONT/D9511

Split Qty: 1

Carton Qty: 20, 20 , 16, 16, 16

www.pulset.com

PULSESET Pty Ltd ABN. 33 095 649 228 All Correspondence: P.O Box 6644, Wetherill Park BC NSW 2164
1300 Pulset (785738) P. +61 2 9756 5000 F. +61 2 9756 6192 E. mail@pulset.com W. www.pulset.com


SYDNEY **MELBOURNE** **ADELAIDE** **BRISBANE** **PERTH** **HOBART**
02 9756 5000 03 9095 7333 08 7221 2999 07 3166 8222 08 6467 7755 03 6281 2422

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Pulset nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.


Project	Code	D4011	D5011	D6500	D8011	D9511
Rated working current (A)	AC 3	40	50	65	80	95
	AC 4	18.5	24	28	37	44
Standard power ratings of 3-phase motors 50/60Hz in category AC-3	220/230V	11	15	18.5	22	25
	380/400V	18.5	22	30	37	45
	415V	22	25	37	45	45
	500V	22	30	37	55	55
	660/690V	30	33	37	45	55
Rated heat current (A)		60	80	80	125	125
Electrical life	AC 3(x10 ⁴)	80	60	60	60	60
	AC 4(x10 ⁴)	15	15	15	10	10
Mechanical life (x10 ⁴)	500V	800	800	800	600	600
Number of the contacts		3P+NC+NO				




CONT/D4011




CONT/D8011



CONT/D5011



CONT/D6511



CONT/D9511

www.pulset.com

PULSESET Pty Ltd ABN. 33 095 649 228 All Correspondence: P.O Box 6644, Wetherill Park BC NSW 2164
1300 Pulset (785738) P. +61 2 9756 5000 F. +61 2 9756 6192 E. mail@pulset.com W. www.pulset.com

SYDNEY MELBOURNE ADELAIDE BRISBANE PERTH HOBART
02 9756 5000 03 9095 7333 08 7221 2999 07 3166 8222 08 6467 7755 03 6281 2422

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Pulset nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.