



CE CB AS/NZS



Technical Specifications

Rated Current	15A Resistive Load.
Rated Voltage(Un)	AC 180V---250V
Rated frequency	50(60)Hz
Hysteresis	≤2s/d (at 25°C)
Dimensions	66mm(L) 82mm(H) 36mm(W)
Installation method	DIN rail
Load capacity	15A 250VAC
On/off operation	8on & 8off
Minimum interval	1MIN
Endurance	≤500000
Operating temperature	-10°C~+55°C
Display	LCD
Battery backup	150h
RCM approval	N5400

www.pulset.com

PULSESET Pty Ltd ABN. 33 095 649 228 All Correspondence: P.O Box 6644, Wetherill Park BC NSW 2164

1300 Pulset (785738) P. +61 2 9756 5000 F. +61 2 9756 6192 E. mail@pulset.com W. www.pulset.com

SYDNEY MELBOURNE ADELAIDE BRISBANE PERTH HOBART

02 9756 5000 03 9095 7333 08 7221 2999 07 3166 8222 08 6467 7755 03 6281 2422

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Pulset nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.



Quality
ISO 9001
SAI GLOBAL