



Dimensions in millimetres.



## Description:

DOL magnetic starter with a working frequency of 50Hz and a rated voltage of up to 550V. Available in 9, 12, 18, 25 and 32Amp. Comply with IEC947-4-1 and has a IP42 rating.

**Material:** The main body adopts alloy or high grade anti-flaming plastic, the contact adopts special alloy, so it has strong anti-electrical erosion protection.

**Application:** Magnetic starter is mainly applied to circuit of AC 50 or 60Hz, voltage up to 550V for far distance making and breaking circuit and frequently starting and controlling motor.

Code	Project	Rated Current(A)	Maximum Power AC3 duty (KW)					660V 690V
			220V 230V	380V 400V	415V	440V	500V	
DOLSTART/D09		9	2.2	4	4	4	5.5	5.5
DOLSTART/D12		12	3	5.5	5.5	5.5	7.5	7.5
DOLSTART/D18		18	4	7.5	9	9	10	10
DOLSTART/D25		25	5.5	11	11	11	15	15
DOLSTART/D32		32	7.5	15	15	15	18.5	18.5

**Split Qty:** 1, 1, 1, 1, 1

**Carton Qty:** 20, 20, 20, 16, 16

[www.pulset.com](http://www.pulset.com)

PULSESET Pty Ltd ABN. 33 095 649 228 All Correspondence: P.O Box 6644, Wetherill Park BC NSW 2164

1300 Pulset (785738) P. +61 2 9756 5000 F. +61 2 9756 6192 E. mail@pulset.com W. [www.pulset.com](http://www.pulset.com)

SYDNEY MELBOURNE ADELAIDE BRISBANE PERTH HOBART

02 9756 5000 03 9095 7333 08 7221 2999 07 3166 8222 08 6467 7755 03 6281 2422

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Pulset nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.